soul form

## NAME AND HARS COMPANY

IDEPENDENCE MALL WEST

HILADELPHIA, PENNSYLVANIA 19105

## DPM 3506

EMERGENCY PHONE: 215 592-3000 (R. & H.) 800 424-9300 (CHEMTREC)



PRODUCT CODE NO.:

6-5117

MATE	RIAL SAFET	Y DATA SHEET		* 100 H			
ECTION I - IDENTIFICATION OF PRODUCT:	-				Section 1995		
RADE NAME Acryloid B-72 (100%)  ORMULA:	reight classification: non-hazardous  chemical name a synonyms: Acrylic resin						
ECTION II _ HAZARDOUS COMPONENTS OF MIXTURES:		TACITY I COLI					
COMPONE	ENT.				WEIGHT	% 'T.L.V.	
Under current OSHA criteria, this matto be non-hazardous.		considered	VIII.		<u>V</u>		
ECTION III _ PHYSICAL DATA;	e dynamic deposition in the	e transmir i more more actività de l'operation de l	anipare e c	n accessor that ever experien	And a speciment with the	en egye en er eller familier (kommuniker) (kommuniker)	
PPEARANCE - ODOR	e e e a a farancia de parelas	a decoupling a condition of April 1884 in	PROBLEM:		Г (О <b>г</b> ) « ком «	oraninge propries et alles at the secretary con-	
Clear granules. Very mild acrylic odor. N.A  POR PRESSURE 68 ?F (MM MERCURY) VAPOR DENSITY (AIR = 1) EVAPORATION							
N°A	ΝΔ			NΔ	医凯德曼氏 电影影影器的影片	ay says was in the es	
etting or freezing point (of) specific gravity (water	7 = 1) ≥ 2 } = 1 de		atile	See See See See	SOLUBILITY IN		
ECTION IV _ FIRE & EXPLOSION HAZARD DATA:	10 No.	<u>l(by weight)</u>	e Constitutiva produ	N.A.	negligi	ble	
ASH POINT OF (METHOD USED)			LOWER	XPLOSION LIN	AIT UPPER	EXPLOSION LIMIT	
		ON CONCENTRATIONS (OZ/				N.A.	
no deta TINGUISHING MEDIA:	a nas promeering 15. 1981	N_A	633 M	N	Δ	OULES), Page 199	
The state of the s	Tatta dagaalan seken			ij.	n 1 mai 21 m	and the second of the second	
FOAM ALCOHOL FOAM CO2 DR	(Y CHEMICAL 19	WATER FOG	отн	ER .	12 (12 <b>5</b> 13) (13 <b>- 1</b> 3) (13 - 13)	and the grant of the state of t	
N.A.	) - 100 - 110	i est victorio para estado.			agresors and a		
		Signal Children (1994)					
USUAL FIRE & EXPLOSION HAZARDS:							
N.A.							
CTION V _ HEALTH HAZARD DATA;	evylanden en en	Secretary property and the secretary before the second section	-	Symplectic and a scale of the same			
RESHOLD LIMIT VALUE:		and the state of the second section of	- Company of the	and the second second			
FECTS OF OVEREXPOSURE:	in, Sadari	toril conficultoril	grania.	adat sus.	Jean vei	Severi Communitive	
Essentially inert, non-toxic material							
		· Commence of the commence of	incir.	1003 Ja	sigasi.		
						and the state of t	
(A.A. property and the second of the second	- 1 - All Control of the Control of						
	ente in the same on the Head		e esta same			Alary and the second second	
ERGENCY AND FIRST AID PROCEDURES		and the second second second	i. Lighter goden		powersky a stage	and the second second second second second second	
Eye Contact: Wash with water to remov		THE STATE OF	100		an ang ang ang ang ang ang ang ang ang a	ang again an	
Ingestion: Induce vomiting and consu	lt a phys	ician ()	17 s (57 f s 5 5 f s (57 f s 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5	向1   内分寸 打 <b>7</b> 4円ひつ でなっ <b>さ</b> 打り			
		THE STATE OF THE S			#fdmu*I	TQA town, A.M	

TOTAL STREET, SECTION OF THE STREET, S	The second secon
CTION VI _ REACTIVITY DATA:	and the second of the second o
TABLETY: UNSTABLE	CONDITIONS TO AVOID:  N.A.1
	acrylic monomers which may evolve on overheating during processing
(AZARDOUS POLYMERIZATION:	CONDITIONS TO AVOID: A CONTRACT OF THE CONTRAC
MAY OCCUR WILL NOT	The Control of the Co
NCOMPATABILITY (MATERIALS TO AVOID): WATER OTHER	$N_i$ , $A_{i,i+1}$ , and $A_{i,i+1}$ , and $A_{i,i+1}$
TECTION VII _ SPILL OR LEAK PROCES	
*Shovel into containers f	or disposal.
M. P. Commission of the Commis	
	Coder correct ESSA of torday, this polyected is constanted
vaste disposal methods: <u>Landfill according to fe</u>	deral, state and local regulations.
ECTION VIII _ SPECIAL PROTECTION	N FORMATION:
TYPE OF VENTILATION	n workroom mir
Adequate to provide cles	n workroom air.
	eriod where dust is apparent.
RDIECTIVE GLOVES	- 트로드 이번 사람들은 이번 전에 대한 사람들은 사람들은 사람들은 사람들이 되었다. 그는 이번 사람들은 사람들은 사람들은 사람들은 사람들은 사람들은 사람들은 사람들은
Canvas gloves	The state of the s
ALEX LOCATION STATE AND STATE OF THE STATE O	
ECTION IX - STORAGE AND LABELING	
INDOOR:	HEATED: REFRIGERATED: OUTDOOR:
YES	
Balandaria de la companio de la comp	STORAGE TEMPERATURE (F):  MAX: MIN:
Store indoors in summer	and keep temperature below 80°F. Granules will agglomerate
at higher temperatures.	
The second secon	
grading out to the second of t	SPACED ENGINEER VENEZA
PRECAUTIONARY LABELING:	201 P. C.
<ul> <li>Saved Market Specifical Control of the Control of the</li></ul>	s the Manufacturing Chemists' Association guide for the labeling of
products which contain h	azardous materials. Please refer to previous sections of this form
and to product labels on	containers.
The Course of the Conference o	REBUILT CONTROL TARE YORK AND AND
	Figure 1 1871 of the 1881 to t
	Tyre Contests Weell will, valer to remove and or particles.
	THE INFORMATION CONTAINED HEREIN IS BASED ON DATA CONSIDERED ACTIONS OF THE CONTRACT OF THE CO
1	THE ACCURACY OF THESE DATA OR THE RESULTS TO BE OBTAINED FROM THE USE THEREOF. VENDOR ASSUMES NO RESPONSIBILITY FOR INJURY TO VENDEE OR THIRD
N.ANot Applicable	PERSON PROXIMATELY CAUSED BY THE MATERIAL IF REASONABLE SAFETY 6-5117 PROCEDURES ARE NOT ADHERED TO AS STIPULATED IN THE DATA SHEET. ADDITIONALLY VENDOR ASSUMES NO RESPONSIBILITY FOR INJURY TO VENDEE
	OR THIRD PERSONS PROXIMATELY CAUSED BY ABNORMAL USE OF THE MA- TERIAL EVEN IF REASONABLE SAFETY PROCEDURES ARE FOLLOWED. FURTHER DATE 11/72
	MORE, VENDER ASSUMES THE RISK IN HIS USE OF THE MATERIAL.